



Safety Data Sheet
Fite's Stain Kit EU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Fite's Stain Kit
Product number	KT013
Brand	Fite's Stain Kit

Other means of identification

Component 1: Xylene-Peanut Oil
Component 2: Acid Alcohol Solution (1%)
Component 3: Carbol Fuchsin Solution
Component 4: Methylene Blue Solution

1.2 Relevant identified uses of the substance or mixture and uses advised against

In Vitro Diagnostic Use

1.3 Details of the supplier of the safety data sheet

Name	Diagnostic Biosystems
Address	6616 Owens Drive Pleasanton CA 94588 USA
Telephone	(888) 896-3350
email	customersupport@dbiosys.com

1.4 Emergency telephone number

(925) 484-3350 (9AM-6PM, Monday - Friday, Pacific Standard Time)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

- Acute toxicity, dermal (chapter 3.1), Cat. 5, H313
- Acute toxicity, inhalation (chapter 3.1), Cat. 4, H332
- Acute toxicity, inhalation (chapter 3.1), Cat. 5, H333
- Skin corrosion/irritation (chapter 3.2), Cat. 2, H315
- Specific target organ toxicity following repeated exposure (chapter 3.9), Cat. 2, H373
- Specific target organ toxicity following single exposure (chapter 3.8), Cat. 3, H335, H336

Safety Data Sheet

Fite's Stain Kit EU

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms



1. Exclamation mark; 2. Health hazard

Signal word

Warning

Hazard statements

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to a licensed disposal company.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component 1. Xylene-Peanut Oil

1. Xylene

Concentration	50 % (volume)
Other names / synonyms	Benzene, dimethyl-; XYLENES (MIXED)
EC no.	215-535-7
CAS no.	1330-20-7
Index no.	601-022-00-9

- Flammable liquids (chapter 2.6), Cat. 3
- Acute toxicity, inhalation (chapter 3.1), Cat. 4
- Acute toxicity, dermal (chapter 3.1), Cat. 4

Safety Data Sheet

Fite's Stain Kit EU

- Skin corrosion/irritation (chapter 3.2), Cat. 2

H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
SCLs/M-factors/ATEs	*

2. *Arachis hypogaea* seedcoat extract

Concentration 50 % (volume)

Other names / synonyms Arachidis oleum; Peanut oil;
CAS no. 8002-03-7

Component 2. Acid Alcohol

1. Alcohol

Concentration 65 % (volume)

Other names / synonyms ABSOLUTE ETHANOL; ALCOHOL DEHYDRATED; ALCOHOL, ANHYDROUS; Alcoholum / ethanolum; ALGRAIN; ANHYDROL; COLOGNE SPIRIT; COLOGNE SPIRITS (ALCOHOL); Ethanol; ETHANOL 200 PROOF; ETHANOL SOLUTION; ETHYL ALCOHOL; ETHYL ALCOHOL ANHYDROUS; ETHYL HYDRATE; ETHYL HYDROXIDE; FERMENTATION ALCOHOL; GRAIN ALCOHOL; JAYSOL; JAYSOL S; METHYLCARBINOL; MOLASSES ALCOHOL; NCI-C03134; POTATO ALCOHOL; SD ALCOHOL 23-HYDROGEN; SPIRIT; SPIRITS OF WINE; TECSOL; UN 1170

EC no. 200-578-6
CAS no. 64-17-5
Index no. 603-002-00-5

- Flammable liquids (chapter 2.6), Cat. 2

H225 Highly flammable liquid and vapor

2. Isopropyl alcohol

Concentration 5 % (volume)

Other names / synonyms 2-HYDROXYPROPANE; 2-Propanol; 2-PROPYL ALCOHOL; ALCOJEL; ALCOSOLVE; ALCOSOLVE 2; AVANTIN; AVANTINE; CHROMAR; COMBI-SCHUTZ; DIMETHYLCARBINOL; HARTOSOL; IMSOL A; ISOHOL; Isopropanol; LUTOSOL; N-PROPAN-2-OL; PETROHOL; PRO; PROPAN-2-OL; Propan-2-ol, isopropanol; PROPOL; reaction mass of: bis(1S,2S,4S)-(1-benzyl-4-tert-butoxycarboxamido-2-hydroxy-5-phenyl)pentylammonium succinate; SEC-PROPYL ALCOHOL; SPECTRAR; STERISOL HAND DISINFECTANT; TAKINEOCOL; UN 1219

EC no. 414-810-0
CAS no. 67-63-0
Index no. 607-403-00-6

Safety Data Sheet

Fite's Stain Kit EU

- Flammable liquids (chapter 2.6), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 2
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3
- Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 1
- Hazardous to the aquatic environment, short-term (acute) (chapter 4.1), Cat. 1
- Hazardous to the aquatic environment, long-term (chronic) (chapter 4.1), Cat. 1

H225	Highly flammable liquid and vapor
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

3. Hydrochloric acid

Concentration	1 % (volume)
Other names / synonyms	Acidum hydrochloricum; hydrogen chloride; HYDROGEN CHLORIDE (gas)
EC no.	231-595-7
CAS no.	7647-01-0
Index no.	017-002-01-X

- Skin corrosion/irritation (chapter 3.2), Cat. 1
- Eye damage/irritation (chapter 3.3), Cat. 1
- Acute toxicity, inhalation (chapter 3.1), Cat. 3

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
SCLs/M-factors/ATEs	Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 % STOT SE 3; H335: C ≥ 10 %

Component 3. Carbol Fuchsin

1. Alcohol

Concentration	10 % (volume)
Other names / synonyms	ABSOLUTE ETHANOL; ALCOHOL DEHYDRATED; ALCOHOL, ANHYDROUS; Alcoholum / ethanolum; ALGRAIN; ANHYDROL; COLOGNE SPIRIT; COLOGNE SPIRITS (ALCOHOL); Ethanol; ETHANOL 200 PROOF; ETHANOL SOLUTION; ETHYL ALCOHOL; ETHYL ALCOHOL ANHYDROUS; ETHYL HYDRATE; ETHYL HYDROXIDE; FERMENTATION ALCOHOL; GRAIN ALCOHOL; JAYSOL; JAYSOL S; METHYLCARBINOL; MOLASSES ALCOHOL; NCI-C03134; POTATO ALCOHOL; SD ALCOHOL 23-HYDROGEN; SPIRIT; SPIRITS OF WINE; TECSOL; UN 1170
EC no.	200-578-6
CAS no.	64-17-5
Index no.	603-002-00-5

Safety Data Sheet

Fite's Stain Kit EU

- Flammable liquids (chapter 2.6), Cat. 2

H225 Highly flammable liquid and vapor

2. PHENOL

Concentration 5 % (volume)
EC no. 203-632-7
CAS no. 108-95-2
Index no. 604-001-00-2

- Germ cell mutagenicity (chapter 3.5), Cat. 2
- Acute toxicity, inhalation (chapter 3.1), Cat. 3
- Acute toxicity, dermal (chapter 3.1), Cat. 3
- Acute toxicity, oral (chapter 3.1), Cat. 3
- Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 2
- Skin corrosion/irritation (chapter 3.2), Cat. 1B

H301 Toxic if swallowed
H311 Toxic in contact with skin
H314 Causes severe skin burns and eye damage
H331 Toxic if inhaled
H341 Suspected of causing genetic defects [route]
H373 May cause damage to organs [organs] through prolonged or repeated exposure [route]

SCLs/M-factors/ATEs

*
Skin Corr. 1B; H314: C ≥ 3 %
Skin Irrit. 2; H315: 1 % ≤ C < 3 %
Eye Irrit. 2; H319: 1 % ≤ C < 3 %

3. Ci 42510

Concentration 0.5 % (weight)

Other names / synonyms (4-(4-Aminophenyl)(4-iminocyclohexa-2,5-dienylidene)methyl)-2-methylaniline hydrochloride; Benzenamine, 4-((4-aminophenyl)(4-imino-2,5-cyclohexadien-1-ylidene)methyl)-2-methyl-, hydrochloride (1:1); Benzenamine, 4-[(4-aminophenyl)(4-imino-2,5-cyclohexadien-1-ylidene)methyl]-2-methyl-, monohydrochloride; C.I. BASIC VIOLET 14; Fuchsin
CAS no. 632-99-5

Component 4. Methylene Blue

1. Alcohol

Concentration 12 % (volume)

Other names / synonyms ABSOLUTE ETHANOL; ALCOHOL DEHYDRATED; ALCOHOL, ANHYDROUS; Alcoholum / ethanolum; ALGRAIN; ANHYDROL; COLOGNE SPIRIT; COLOGNE SPIRITS (ALCOHOL); Ethanol; ETHANOL 200 PROOF; ETHANOL SOLUTION; ETHYL ALCOHOL; ETHYL ALCOHOL ANHYDROUS; ETHYL HYDRATE; ETHYL HYDROXIDE; FERMENTATION

Safety Data Sheet

Fite's Stain Kit EU

ALCOHOL; GRAIN ALCOHOL; JAYSOL; JAYSOL S; METHYLCARBINOL;
MOLASSES ALCOHOL; NCI-C03134; POTATO ALCOHOL; SD ALCOHOL
23-HYDROGEN; SPIRIT; SPIRITS OF WINE; TECSOL; UN 1170

EC no. 200-578-6
CAS no. 64-17-5
Index no. 603-002-00-5

- Flammable liquids (chapter 2.6), Cat. 2

H225 Highly flammable liquid and vapor

2. Isopropyl Alcohol

Concentration 0.5% (volume)

Other names / synonyms 2-HYDROXYPROPANE; 2-Propanol; 2-PROPYL ALCOHOL; ALCOJEL;
ALCOSOLVE; ALCOSOLVE 2; AVANTIN; AVANTINE; CHROMAR; COMBI-
SCHUTZ; DIMETHYLCARBINOL; HARTOSOL; IMSOL A; ISOHOL;
Isopropanol; LUTOSOL; N-PROPAN-2-OL; PETROHOL; PRO; PROPAN-2-
OL; Propan-2-ol, isopropanol; PROPOL; reaction mass of: bis(1S,2S,4S)-(1-
benzyl-4-tert-butoxycarboxamido-2-hydroxy-5-phenyl)pentylammonium
succinate; SEC-PROPYL ALCOHOL; SPECTRAR; STERISOL HAND
DISINFECTANT; TAKINEOCOL; UN 1219

EC no. 414-810-0
CAS no. 67-63-0
Index no. 607-403-00-6

- Flammable liquids (chapter 2.6), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 2
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3
- Specific target organ toxicity, repeated exposure (chapter 3.9), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 1
- Hazardous to the aquatic environment, short-term (acute) (chapter 4.1), Cat. 1
- Hazardous to the aquatic environment, long-term (chronic) (chapter 4.1), Cat. 1

H225 Highly flammable liquid and vapor
H318 Causes serious eye damage
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H373 May cause damage to organs through prolonged or repeated exposure
H400 Very toxic to aquatic life
H410 Very toxic to aquatic life with long lasting effects

3. Methylene Blue anhydrous

Concentration 0.2 % (weight)

Other names / synonyms Phenothiazin-5-ium, 3,7-bis(dimethylamino)-, chloride
EC no. 200-515-2
CAS no. 61-73-4

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes	Consult a physician. Show this safety data sheet to the doctor in attendance.
Following inhalation	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Following skin contact	Rinse with plenty of water. Get medical attention if irritation develops and persists.
Following eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Following ingestion	Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.
Self-protection of the first aider	Ensure adequate ventilation. Use personal protective equipment. For personal protection see section 8.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Use extinguishing media appropriate for surrounding fire.

5.2 Special hazards arising from the substance or mixture

Ethanol: Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Further information

No data available.

SECTION 6: Accidental release measures

Safety Data Sheet

Fite's Stain Kit EU

6.1 Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

Ensure adequate ventilation. Use personal protective equipment. For personal protection see section 8.

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Should not be released into the environment. See Section 12 for additional ecological information.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

CAS: 108-95-2

Phenol

Cal/OSHA: 5 ppm PEL inhalation; NIOSH: 5 ppm, (C) 15.6 ppm [15-min] REL inhalation; OSHA: 5 ppm PEL inhalation; 19 mg/m³ PEL inhalation

CAS: 1330-20-7

Xylene

Cal/OSHA: 100 ppm, (ST) 150 ppm, (C) 300 ppm PEL inhalation; NIOSH: 100 ppm, (ST) 150 ppm REL inhalation; OSHA: 100 ppm PEL inhalation; 435 mg/m³ PEL inhalation

CAS: 64-17-5

Alcohol

ACGIH (USA): (ST) 1000 ppm TLV[®] inhalation; Cal/OSHA: 1000 ppm PEL inhalation; NIOSH: 1000 ppm REL inhalation; OSHA: 1000 ppm PEL inhalation; 1900 mg/m³ PEL inhalation

CAS: 67-63-0

Isopropyl alcohol

Safety Data Sheet

Fite's Stain Kit EU

ACGIH (USA): 200 ppm, (ST) 400 ppm TLV® inhalation; Cal/OSHA: 400 ppm, (ST) 500 ppm PEL inhalation; NIOSH: 400 ppm, (ST) 500 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 980 mg/m3 PEL inhalation

CAS: 7647-01-0

Hydrochloric acid

ACGIH: 2 ppm (C) TLV® inhalation; NIOSH: 5 ppm, 7 mg/m3 REL-C inhalation; OSHA: 5 ppm, 7 mg/m3 PEL-C inhalation

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Individual protection measures, such as personal protective equipment

Pictograms



Eye and face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Thermal hazards

No data available

Control banding approach

No data available.

Environmental exposure controls

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state
Appearance
Colour
Odour

Liquid
Clear and colored dyes
Various dyes
Alcohol

Safety Data Sheet

Fite's Stain Kit EU

Odour threshold	No data available.
pH	No data available
Melting point/freezing point	No data available.
Boiling point or initial boiling point and boiling range	No data available.
Flash point	No data available.
Evaporation rate	No data available.
Flammability	No data available.
Lower and upper explosion limit/flammability limit	No data available.
Vapor pressure	No data available.
Relative vapor density	No data available.
Density and/or relative density	No data available.
Solubility	No data available.
Partition coefficient n-octanol/water (log value)	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	No data available.
Kinematic viscosity	No data available.
Explosive properties	No data available.
Oxidizing properties	No data available.

Particle characteristics

No data available.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

No data available.

9.2.2 Other safety characteristics

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

None under normal use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

None under normal use conditions.

10.4 Conditions to avoid

Exposure to moisture.

Avoid storing in direct sunlight and avoid extremes of temperature.

Heat, flames and sparks.

10.5 Incompatible materials

Ethanol: Alkali metals, Oxidizing agents, Peroxides

Isopropanol: Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids

10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

Safety Data Sheet

Fite's Stain Kit EU

Isopropanol: Hazardous decomposition products formed under fire conditions. - Carbon oxides
Other decomposition products - No data available
In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Ethanol: ACGIH: A3 Confirmed animal carcinogen with unknown relevance to humans.

The ATE (dermal) of the mixture is: 2122.19 mg/kg bw

The ATE (gas inhalation) of the mixture is: 7974.68 ppmV

The ATE (vapor inhalation) of the mixture is: 20.5 mg/l

Skin corrosion/irritation

ETHANOL

LD50 Skin - Rabbit - 15,800 mg/kg

ISOPROPANOL

LD50 Skin - Rabbit - 12,800 mg/kg

Serious eye damage/irritation

ETHANOL

OECD Test Guideline 405 Eyes - Rabbit

Result: Moderate eye irritation

Respiratory or skin sensitization

ETHANOL

LD50 Skin - Rabbit - 15,800 mg/kg

ETHANOL

LD50 Inhalation - Rat - 30,000 mg/l - 4 h

ETHANOL

OECD Test Guideline 404 Skin - Rabbit - 24 h

Result: No skin irritation

ISOPROPANOL

LC50 Inhalation - Rat - 16000 ppm - 8 h

ISOPROPANOL

LD50 Skin - Rabbit - 12,800 mg/kg

Germ cell mutagenicity

Based on available data, classification data are not met

is product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Carcinogenicity

Safety Data Sheet

Fite's Stain Kit EU

ISOPROPANOL

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Based on available data, classification data are not met

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

ETHANOL

EC50 - *Chlorella vulgaris* (Fresh water algae) - 275 mg/l - 72 h

ETHANOL

LC50 - *Pimephales promelas* (fathead minnow) - 14,200 mg/l - 96 h

ETHANOL

LC50 - *Ceriodaphnia dubia* (water flea) - 5,012 mg/l - 48 h

ISOPROPANOL

LC50 - *Pimephales promelas* (fathead minnow) - 9,640.00 mg/l - 96 h

ISOPROPANOL

EC50 - *Daphnia magna* (water flea) - 5,102.00 mg/l - 24 h

ISOPROPANOL

EC50 - *Daphnia magna* (water flea) - 6,851 mg/l - 24 h

ISOPROPANOL

EC50 - *Desmodesmus subspicatus* (chodat) - > 2,000.00 mg/l - 72 h

ISOPROPANOL

EC50 - Algae - > 1,000.00 mg/l - 24 h

Safety Data Sheet

Fite's Stain Kit EU

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product disposal

Offer surplus and non-recyclable solutions to a licensed disposal company.

Packaging disposal

Dispose of as unused product.

Waste treatment

No data available

Sewage disposal

Do not let product enter drains

Other disposal recommendations

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport information

14.1	UN Number	UN1987
14.2	UN Proper Shipping Name	Alcohols, n.o.s.
14.3	Transport hazard class(es)	3
14.4	Packing group	I
14.5	Environmental hazards	None
14.6	Special precautions for user	None
14.7	Maritime transport in bulk according to IMO instruments	None

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment

The supplier of this product has not conducted any Chemical Safety Assessment

HMIS Rating

Safety Data Sheet

Fite's Stain Kit EU

Fite's Stain Kit EU	
HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	G

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

H313	May be harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H333	May be harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

SDS-0126, Rev. A

Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Diagnostic BioSystems be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Diagnostic BioSystems has been advised of the possibility of such damages.